

SIMPLE

ordering by e-mail

Ordering code for ball nuts

<input type="text"/>	-	<input type="text"/>								
1		2		3		4		5		6

No.	Identification	Code	Description
1	Product abbreviation	KGMF	Flanged ball nut
		KGMZ	Cylindrical ball nut
2	Nut type	D	Nut according to standard DIN 69051
		W	Nut according to Wandel standard
		S	Nut with special dimensions
3	Thread designation		Nominal diameter/pitch, e.g. 3205
4	Pitch direction	RH	Right-hand thread (standard)
		LH	Left-hand thread (upon request)
5	Seal	0	Without wiper ring
		EE	With double-sided wiper ring
6	Special requirements	0	None
		1	According to specifications, description or drawing

Ordering code for ball screws

<input type="text"/>	-	<input type="text"/>																				
1		2		3		4		5		6		7		8		9		10		11		12

No.	Identification	Code	Description
1	Product abbreviation	KGT	Ball screw
2	Spindle type	R	Rolled
		W	Spun
		S	Ground
3	Thread designation		Nominal diameter/pitch, e.g. 3205
4	Lead accuracy of the spindle	T5	23µm / 300mm
		T7	50µm / 300mm
		T9	130µm / 300mm
		T10	200µm / 300mm
5	Pitch direction	RH	Right-hand thread (standard)
		LH	Left-hand thread (upon request)
6 7	Spindle end A Spindle end B	0	Ends just sawn and brushed
		A	End with chamfer
		GA	1st end annealed (state length in additional information)
		GB	2nd end annealed (state length in additional information)
		K	End according to customer or project drawing
		D	Standard end fixed bearing for bearing ZKLF
		F	Standard end fixed bearing for bearing ZARN
		H	Standard end fixed bearing for bearing ZARF/LTN
		J	Standard end fixed bearing for bearing FDX
		L	Standard end fixed bearing for angular contact ball bearing
		S	Standard end movable bearing for deep-groove ball bearing
T	Standard end movable bearing for needle bearing		
W	Standard end movable bearing for deep-groove ball bearing		
8	Overall length		e.g. 1000 (mm)
9	Special requirements spindle	0	None
		1	According to specifications, description or drawing
10	Ball nut or nut unit with installation instructions	Z	Single nut, cylindrical
		F0	Flanged single nut (flange to fixed bearing or longer end)
		0F	Flanged single nut (flange to movable bearing or shorter end)
		ZZ	Double nut unit, cylindrical/cylindrical
		FZ	Double nut unit flanged/cylindrical (flange to fixed bearing or longer end)
		ZF	Double nut unit flanged/cylindrical (flange to movable bearing or shorter end)
		FF	Double nut unit flanged/flanged
11	Nut type	D	Nut according to standard DIN 69051
		W	Nut according to Wandel standard
		S	Nut with special dimensions (according to drawing)
12	Special requirements for nut	0	None
		1	According to specifications, description or drawing

You can order ball nuts and ball screws quickly and easily. Using the list on the left, simply combine the appropriate ordering code by selecting each block in turn: six blocks for each ball nut; twelve blocks for each ball screw.

Enter these codes in the order form and send it by e-mail to:

a.armbruster@wandel-cnc.com